

EASI6002

EASITRADE 18W 4000K IP20 Slimline Downlight



General Details

Finish	Matte White Finish
Product Weight	0.9KG
Overall Dimensions	ø235mm x 11mm / Cut Out ø215
Carton Weight / Material	1.20 kg / Cardboard
Packaging Sizes / Packed Weight	Length 250mm, Height 90mm, Width 250mm
Packaging & Labelling Guidelines	Saturn LED.eu - Generic labelling
Bar Coding	Saturn LED coding in accordance with EAN-12 & ITF-14
IP Rating	IP20
Energy Rating	A* - (Very Low Energy)





Light Source

Rated Wattage	18W
Lumens	1620
Lumens Per Watt	90
Recommended Product Location	Interior - Stairwell / Office Lighting
Light Source Brand	Epistar LED Chips
Colour Temperature	4000K
CRI Ra	Ra > 80
Lifespan	50,000 Hours
Lamp Working Temperature	<50°C
Beam Angle	110°
Photometric Data	Visit www.saturnled.eu for full Photometric files
Lamp Code	N/A

Electrical

Voltage	220-240V. 50 / 60Hz. AC.
Charge Current (I)	0.10A
Electrical Classification	Class II. (Double Insulated LED Driver). SELV
Cabling Electrical Connections	Screw fix in terminal block
LED Driver	Pri.220-240VAC/Sec:350mA Max DC26V

Installation

Distance from Illuminated Object	0.5m
Method of Fix	Ceiling Recessed
Recommended Working Temperature	Minimum Temp -10°C to Maximum Temp + 40°C
Instruction Sheet	Supplied with product





Origin & Markets

Country of Manufacture	Designed & tested in Europe - Manufactured in China
Intended Market	Europe, Middle East & Australia 220 - 240Volt

Materials

Main Housing Material	Die Cast Aluminium Powder Coated Body
Fixings Main Housing	Steel screws
Front Shield	Frosted PC diffuser

Approvals

www.saturnled.eu/warranty
8



