



MASTER TL-D Super 80

MASTER TL-D Super 80 18W/830 1SL/25

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous efficacy (rated) (nom.)	
Cap base	G13 [Medium Bi-Pin Fluorescent]		75 lm/W
Life to 10% failures (nom.)	12000 h	Colour rendering index (nom.)	>80
Life to 50% failures (nom.)	15000 h	LLMF 2000 h Rated	96 %
Life to 50% failures preheat (nom.)	20000 h	LLMF 4000 h Rated	95 %
LSF 2000 h Rated	99 %	LLMF 6000 h Rated	94 %
LSF 4000 h Rated	99 %	LLMF 8000 h Rated	93 %
LSF 6000 h Rated	99 %	LLMF 12000 h Rated	92 %
LSF 8000 h Rated	99 %	LLMF 16000 h Rated	91 %
LSF 12000 h Rated	89 %	LLMF 20000 h Rated	90 %
LSF 16000 h Rated	33 %		
LSF 20000 h Rated	2 %	Operating and Electrical	
		Power (Rated) (Nom)	18.0 W
		Lamp current (nom.)	0.360 A
Light Technical		Temperature	
Colour Code	830 [CCT of 3,000 K]	Design temperature (nom.)	25 °C
Luminous flux (nom.)	1350 lm		
Luminous flux (rated) (nom.)	1350 lm		
Colour designation	Warm white (WW)		
Correlated Colour Temperature (Nom)	3000 K		

MASTER TL-D Super 80

Controls and Dimming

Dimmable	Yes
----------	-----

Approval and Application


Energy efficiency label (EEL)	A
Mercury (Hg) content (nom.)	2.0 mg
Energy consumption kWh/1,000 hours	22 kWh

Product Data

Full product code	871150063165740
Order product name	MASTER TL-D Super 80 18W/830 1SL/25

EAN/UPC – product	8711500631657
Order code	63165740
Local code	18830
SAP numerator – quantity per pack	1
Numerator – packs per outer box	25
Material no. (12 NC)	927920083023
SAP net weight (piece)	71.000 g
ILCOS code	FD-18/30/1B-E-G13


Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Super 80 18W/830 1SL/25	28 mm	589.8 mm	596.9 mm	594.5 mm	604 mm

TL-D 18W/830

Photometric data



Lightcolour /830



Lightcolour /830

MASTER TL-D Super 80

Lifetime



LDLE_TL-D8_0001-Life expectancy diagram

LDLE_TL-D8_0002-Life expectancy diagram



LDLM_TL-D8_0001-Lumen maintenance diagram

